

Appendix A: Programming overview

Default settings are shown in bold.

A. Configuration	B. Administration	C. Maintenance
1. Telephony Data Dial delay: 1000 B03 Gain Values PBX-CPP +0 CPP-PBX +0 PBX-RAD +0 RAD-PBX +0 TONE-PBX +0 Side tone: On CMCC slot DTMF Timing ¹ Tone burst: 120 Interdigit: 80 Pause: 1500 PCM mode: Mu Law	1. Registration Mstr Reg Enbl: N WTN Reg. Status Show WTN:	1. System Status MC CT2PLUS

A. Configuration	B. Administration	C. Maintenance
2. Mobility Data Reevaluation Re-Eval status Re-Eval schedule	2. User Options Radio loss hdlng Change Default Dflt Change WTN:	2. Card Status Show Card Version
Radios Show Radio:_ Cell Assignment Antenna Type	3. Time and Date Time Date	3. WTN Status Show WTN
Cells Show Cell:_ Cell radios	4. Passwords Admin. password Reg. password	4. TCM Status Show TCM
System LID		5. Evnt/Alrm Log
3. Admin set data Installer password Set languages ² 1: English 2: English 3: English		6. Admin Log

1. DTMF timing and PCM mode settings are available only when you choose the custom country settin.

2. Set languages is available only when you choose the custom country setting.